



Z-Ultimate® 3000T White

Autoclave/ sterilisation labels

Thermal Transfer Material

Description:

A top coated white gloss polyester thermal transfer label stock with excellent print quality. Coated specially for use with Zebra 5095 resin thermal transfer ribbon to produce outstanding print quality and image durability. High-strength acrylic adhesive offers superior strength and adhesion for a wide variety of surfaces. Unparalleled smear/scratch resistance for a thermal transfer label.

Note: Z-Ultimate 3000T White is not to be used for fanfold applications.

Empfohlene Anwendungen

- resistent gegen Sterilisationsverfahren (z.B. für Instrumentenkennzeichnung)
- resistent gegen Säure oder alkalische Lösungen
- kann unter Wasser getaucht werden

Technical Specifications

	Description	Caliper
Facestock	White pearlescent coated polyester	50 microns
Adhesive	Permanent acrylic	20 microns
Liner	65gsm Glassine liner	56 microns
	Total	126 microns

Recommended Zebra Ribbons: 4800, 5095, 5100

Recommended Zebra printers: desktop, mid-range and high-performance

Minimum Application Temperature: 10°C

Service Temperature Range: -40°C to 150°C

Recommended Storage Conditions: One year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

All information on this document is to be used for guidance only and is not to be used for setting specifications. All purchasers of Zebra products shall be responsible for independently determining if the product conforms to all requirements of the application.

For testing of this material, please order SAM5164.